

PRODUCT DATASHEET Sandra series



	Orderin Descrip
	Family
1500 00 100	Туре
	LED
	Color
	Diamete
	Height
	Style
	Optic Ma
	Holder N
	Fastenin
	Status



Ordering number Description	C11814 C11814_Sandra-12-M-XP		
Family	Sandra	FWHM	28 degrees
Туре	Lens	Efficiency	-
LED	XP-E	cd/lm	-
Color	Transparent	Gerber File	Available
Diameter	67 mm		
Height	11.1 mm		
Style	Round		
Optic Material	PMMA		
Holder Material	-		
Fastening	Glue		
Status	Ready		
Ordering number Description	C11700 C11700-Sandra-12-W-XP		
		FWHM	36 degrees
Description	C11700-Sandra-12-W-XP	FWHM Efficiency	36 degrees -
Description Family	C11700-Sandra-12-W-XP Sandra		36 degrees - -
Description Family Type	C11700-Sandra-12-W-XP Sandra Lens	Efficiency	36 degrees - - Available
Description Family Type LED	C11700-Sandra-12-W-XP Sandra Lens XP-E	Efficiency cd/lm	-
Description Family Type LED Color	C11700-Sandra-12-W-XP Sandra Lens XP-E Transparent	Efficiency cd/lm	-
Description Family Type LED Color Diameter	C11700-Sandra-12-W-XP Sandra Lens XP-E Transparent 67 mm	Efficiency cd/lm	-
Description Family Type LED Color Diameter Height	C11700-Sandra-12-W-XP Sandra Lens XP-E Transparent 67 mm 11.1 mm	Efficiency cd/lm	-
Description Family Type LED Color Diameter Height Style	C11700-Sandra-12-W-XP Sandra Lens XP-E Transparent 67 mm 11.1 mm Round	Efficiency cd/lm	-
Description Family Type LED Color Diameter Height Style Optic Material	C11700-Sandra-12-W-XP Sandra Lens XP-E Transparent 67 mm 11.1 mm Round	Efficiency cd/lm	-

NOTE: The typical divergence will be changed by different color, chip size and chip position tolerance. The typical total divergence is the full angle measured where the luminous intensity is half of the peak value.



GENERAL INFORMATION

- Product series especially designed & optimized for XP-E series of LEDs.

- Special care taken to make light distribution as uniform as possible.

- Lens material optical grade PMMA with high UV and temperature resistance (105 degrees of Celcius / 220 degrees of Fahrenheit). Allows use of high current and temperature conditions.

Please find more information about used material from below:

http://ledil.fi/sites/default/files/Documents/Technical/Material/PMMA%208N%20UL94_Yellow%20Card.pdf http://ledil.fi/sites/default/files/Documents/Technical/Material/PMMA%208N%20PLEXIGLAS-Datasheet.pdf

- Fastening to PCB with appropriate adhesive. By clicking link below you can find Ledil recommended glue options.

http://www.ledil.com/datasheets/DataSheet_GLUES.pdf

NOTE 1: We advise customer to ensure the suitability and sufficiency of the bond in the end product. For example, mechanical stress, vibration and holes on the surface of the circuit boar weaken the strength of the glue.

NOTE 2: All surfaces where glue is applied must be clean, dry and free from grease and dirt. If cleaning of PCB surfaces is needed, please follow strictly the cleaning instructions of your LED manufacturer -this is important as cleaning shall under no circumstances damage LEDs or other electronics components on the PCB.

Further note that optical components shall not be cleaned with any chemicals - only micro fiber cloth may be used to remove fingerprints or other traces from handling.

